

MISSOURI DEPARTMENT OF HEALTH STATE PUBLIC HEALTH LABORATORY

BREATH ALCOHOL PROGRAM

DATAMASTER MAINTENANCE REPORT

		<u> </u>	who never instrument
Complete this report in duplicate at the time of the regular ris repaired. Send copy to Department of Health; retain original is	nonthly preventive mainter n department file.	hance check, and	Whenever instrument
is repaired. Send copy to Department of Figure 1	7110	LULI LA BATE OF ING	DECTION
The state of the s		TIME OF INS	2-2009 PECTION DO HES
ST CLAIR COUNTY SAIL, OSCED	nd to be satisfactory or if o	perating within est	ablished limits. (Write
CHECKLIST: Place a check (*) to the left of each item in our in observed values where determined.) Unchecked items must left of each items must left o	pe corrected before using in	nstrument.	
DIAGNOSTIC CHECK (PRINTOUT ATTACHED)			
COMPUTER	DETECTOR		
[Uprogram .	FILTERS		
THEATERS SAMPLE CHAMBER 50 °C	QUARTZ STANDAR	D	
FLOW DETECTOR	CALIBRATION		
[] FUMP HIGH SPEED	PRINTER		
DINDICATOR LIGHTS			
TIME AND DATE			
SIMULATOR TEMPERATURE (34 °C ± 0.2°C) (34,	/ •)	·	
		of the standard V	alue and must have a
Run three tests using a standard solution. All three tests using a standard solution. All three tests spread of .005 or less. Check the box corresponding to RECIRCULATION PUMP)	the standard solution bein	g used. (PRINTO	UT ATTACHED) (USE
11201100211100211000501			
□ 0.100% STANDARD - MUST READ BETWEEN 0.095% □ 0.040% STANDARD - MUST READ BETWEEN 0.038%	and 0.042% INCLUSIVE		
□ 0.100% STANDARD - MUST READ BETWEEN 0.095% □ 0.040% STANDARD - MUST READ BETWEEN 0.038% (ONLY ONE STANDARD IS TO BE USED PER MAINTEN	ANCE REPORT)	recra ter	09
DI 2040W STANDARD - MUST READ BETWEEN 0.038%	and 0.042% INCLUSIVE	TEST 3	,099
O.040% STANDARD - MUST READ BETWEEN 0.038% (ONLY ONE STANDARD IS TO BE USED PER MAINTEN TEST 1 TEST 2 TEST 2 PERFORM R.F.I. TEST (PRINTOUT ATTACHED)	iance report)		
Only one standard is to be used per Mainten TEST 1	iance report)		
ONLY ONE STANDARD - MUST READ BETWEEN 0.038% (ONLY ONE STANDARD IS TO BE USED PER MAINTEN TEST 1 TEST 2 TEST 2 DEFINITION ATTACHED) UNU: ABER OF REFUSALS, SINCE LAST MAINTENANCE FOLLOWS: (DO NOT INCLUDE SIMULATOR TESTS)	ANCE REPORT) , DA 8 REPORT, AND NUMBER OF	BREATH TESTS	IN EACH RANGE AS
ONLY ONE STANDARD - MUST READ BETWEEN 0.038% (ONLY ONE STANDARD IS TO BE USED PER MAINTEN TEST 1	ANCE REPORT) , DA 8 REPORT, AND NUMBER OF (.1014) on that was made to restor	BREATH TESTS 1519) re the instrument	IN EACH RANGE AS (Over .19) to operate satisfactorily
Only one standard is to be used per Mainten TEST 1 TEST 2 TEST 2 Debet 1 Test 2 Test 2 Debet 2 Test 2 Debet 3 Test 2 Test 2 Debet 4 Test 2 Test 2 Debet 4 Test 2 Test 2 Debet 5 Test 2 Debet 6 Test 2 Debet 6 Test 2 Debet 7 Test 2 Debet 8 Test 2 Debet 9 Test 2	ANCE REPORT) , DA 8 REPORT, AND NUMBER OF (.1014) on that was made to restor	BREATH TESTS 1519) re the instrument	IN EACH RANGE AS (Over .19) to operate satisfactorily
ONLY ONE STANDARD - MUST READ BETWEEN 0.038% (ONLY ONE STANDARD IS TO BE USED PER MAINTEN TEST 1	ANCE REPORT) , DA 8 REPORT, AND NUMBER OF (.1014) on that was made to restor (.11) WITHIN DHSS	BREATH TESTS 1519) The the instrument SPECIF	(Over .19) Ø to operate satisfactorily
ONLY ONE STANDARD - MUST READ BETWEEN 0.038% (ONLY ONE STANDARD IS TO BE USED PER MAINTEN TEST 1	and 0.042% INCLUSIVE IANCE REPORT) , D98 REPORT, AND NUMBER OF (.1014) on that was made to restor WITHIN DHSS	BREATH TESTS 1519) The the instrument SPECIF	(Over .19) Ø to operate satisfactorily
ONLY ONE STANDARD - MUST READ BETWEEN 0.038% (ONLY ONE STANDARD IS TO BE USED PER MAINTEN TEST 1	ANCE REPORT) , DA 8 REPORT, AND NUMBER OF (.1014) on that was made to restor (.11) WITHIN DHSS	BREATH TESTS 1519) The the instrument SPECIF	(Over .19) Ø to operate satisfactorily
ONLY ONE STANDARD - MUST READ BETWEEN 0.038% (ONLY ONE STANDARD IS TO BE USED PER MAINTEN TEST 1	and 0.042% INCLUSIVE IANCE REPORT) , D98 REPORT, AND NUMBER OF (.1014) (.1014) (.1014) On that was made to restor WITHIN PHSS (.10-15-2009)	BREATH TESTS 1519) The the instrument SPECIF 340 10	(Over .19) Ø to operate satisfactorily
ONLY ONE STANDARD - MUST READ BETWEEN 0.038% (ONLY ONE STANDARD IS TO BE USED PER MAINTEN TEST 1	and 0.042% INCLUSIVE IANCE REPORT) , D98 REPORT, AND NUMBER OF (.1014) on that was made to restor WITHIN DHSS	BREATH TESTS 1519) The the instrument SPECIF 340 10	(Over .19) Ø to operate satisfactorily



CERTIFICATE OF ANALYSIS

Certified Alcohol Reference Solution for Simulator

Random Samples of Lot Number 08340 of Alcohol Reference Solution for Simulator were analyzed by gas chromatography and found to contain 0.1211 percent (w/vol) ethyl alcohol. The expiration date for this lot number is October 15, 2009 at 11:59 PM.

When used in a calibrated Simulator, operating at 34°C +/- .2°C, this solution will give a breath alcohol analysis instrument reading of 0.10 percent BAC.

The alcohol and wat used in this solution were free of test interfering substances.

fed L. Pauley, President GUTH LABORATORIES, INC.

Face This Side Down - This Edge In First

BAC DataMasterEvidence Ticket

MISSOURI STATE HIGHWAY PATROL DEC DATAMASTER SERIAL MUMBER 284186 06702789

HMOLET TIME: 180 60

CURRECT MEMB:
NOTION

ORB: 050 MBOLET SEX: M

STATE MELT: MOLEOWORGS

MERCHON

OFFICER 1.0.1 290

TESTING UFFICER:
AUSHING

OFFICER 1.0.1 290

TESTING UFFICER:
PERMIT MUMBER: 920004

EXPLOSELEMENTS

MISCELEMENTS OFFI

-- BEHILD HELYSIN ---

ROBER MILESPERED TO

Face This Side Down – This Edge In First

BAC DataMasterEvidence Ticket

MISSOURI STATE HIGHWAY PATROL BAC DATAMASTER SERIAL NUMBER 204188 86/02/09 19:00

--- WHASHOSTIC CHECK ---

CONFITER:	(IKEY
PROGRAM:	OKRY
HERTERS SHIPLE CHRIBERS	Silve.
FLOW DETECTOR:	OKHY
李代明日 長19日 医光芒尼耳炎	UKAY
DETECTOR:	OK HS
FULLERSA	OKAY
到指案T2 三年的114位12	OKAY
U Jan Ieration	OKHY

PROHIER TEST

!"\$4x81(7*+,~./6123456789;;<=>?WHBCULF6 HIGKLMNOPORSTUVWKYZ(NI^) bbcde(ghijklmno pgrstuwwaz(1)="

	HA MA	1/2
Operator Signature	<u> </u>	I / Summer

Printed on recycled paper with agri-based inks

CMSU

Operator Signature

Printed on recycled paper with agri-based inks

CMSU 2208-02

🤏 🖟 Face This Side Down – This Edge In First

BAC DataMasterEvidence Ticket

MISSOURI STATE HIGHWAY PATROL MC DATAMASTER SERIAL MUMBER 204100 06/02/09

TENTING OFFICER:
SUSHABN
OFFICER J.B.: 231
PERMIT MUMBER: 928984
EXPIRATION DATE: 01/15/1)
MISCELLAMEDUS DATA:
LUME MEINTENETICE
ST CLAIR COUNTY

--- SUPERVISOR NODE ---

BLATK TEST	. 849	19106
INTERNAL STANDARD	VERIFIED	19165
EXTERNOL STAIDERD	.097	19:05
RURK TEST	. 606	19106
EXTERNAL STRUBBLE	. 698	19107
BLANK TEST	. 966	19:07
EXTERNAL STANDARD	. 399	19:58
挺滑帐 注約	. 566	19146

SIH. - .1 HVM. - .898

Operator Signature_

Printed on recycled paper with agri-based inks

CMSU 2208-02

State of Missouri DEPARTMENT OF HEALTH



PERMIT TYPE II



W.MITCHELL BUSH

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field repairs, and operate the following breath analyzer(s):

DATAMASTER

for the determination of the alcoholic content of blood from a sample of expired (alveolar) air. Issued under the provisions of sections 577.020 through 577.041, RSMo 1986.

Date 01/15/09

Number **920**004

01/15/2011

MO 580-0771 (7-88)

John of Mathewson

Director of State Public Health Laboratory

Director, Department of Health

Lab. 4 (177-88)